

SECTION 1: Identification

1.1. Identification

Product form : Mixture
 Product name : UC-TG SILICA BLEND
 Product code : UC-TG SILICA BLEND
 Other means of identification : UC-TG SILICA BLEND/32 R

1.2. Relevant identified uses of the substance or mixture and uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Protective Industrial Polymers
 7875 Bliss Parkway
 North Ridgeville, Ohio 44039 - USA-Ohio
 T 440-327-0015
www.protectpoly.com

1.4. Emergency telephone number

Emergency number : Chemtrec: 800-427-9300 (Outside USA) 703-527-3887

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Skin corrosion/irritation, Category 2 H315
 Carcinogenicity, Category 1A H350

Full text of H statements : see section 16

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



GHS07

GHS08

Signal word (GHS-US) : Danger
 Contains : Silicon Dioxide
 Hazard statements (GHS-US) : H315 - Causes skin irritation
 H350 - May cause cancer (Inhalation)
 Precautionary statements (GHS-US) : P201 - Obtain special instructions before use
 P202 - Do not handle until all safety precautions have been read and understood
 P264 - Wash hands thoroughly after handling
 P280 - Wear protective gloves
 P302+P352 - If on skin: Wash with plenty of soap
 P308+P313 - If exposed or concerned: Get medical advice/attention
 P321 - Specific treatment (see a doctor if symptoms do not go away. on this label)
 P332+P313 - If skin irritation occurs: Get medical advice/attention
 P362+P364 - Take off contaminated clothing and wash it before reuse
 P405 - Store locked up
 P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards

Other hazards not contributing to the classification : Prolonged exposure to respirable crystalline silica can cause silicosis.

2.4. Unknown acute toxicity (GHS US)

Not applicable

UC-TG SILICA BLEND

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Portland cement	(CAS No) 65997-15-1	10 - 85	Skin Irrit. 2, H315
Silicon Dioxide	(CAS No) 14808-60-7	0 - 42.5	Carc. 1A, H350
calcium silicate clays	(CAS No) 92704-41-1	5 - 15	Skin Irrit. 2, H315
Calcium Magnesium Hydroxide	(CAS No) 39445-23-3	0 - 5	Not classified

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : Remove the victim into fresh air.
First-aid measures after skin contact : When symptoms occur: rinse immediately with plenty of water.
First-aid measures after eye contact : Rinse immediately with plenty of water.
First-aid measures after ingestion : If the quantity ingested is significant, seek medical attention.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after skin contact : Causes skin irritation.
Symptoms/injuries after eye contact : May cause slight irritation.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Use extinguishing media for surrounding fire.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : No fire hazard.

5.3. Advice for firefighters

No additional information available

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Emergency procedures : Prevent dust cloud formation.

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

No special environmental precautions required.

6.3. Methods and material for containment and cleaning up

- For containment : Collect spillage.
Methods for cleaning up : Collect spillage.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Avoid contact with skin. Avoid dust formation. Avoid raising dust.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store in a dry place.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

UC-TG SILICA BLEND

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Portland cement (65997-15-1)		
ACGIH	ACGIH TWA (mg/m ³)	1 mg/m ³ (Portland cement; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Respirable fraction. The value is for particulate matter containing no asbestos and < 1% crystalline silica)
Not applicable		
calcium silicate clays (92704-41-1)		
ACGIH	ACGIH TWA (mg/m ³)	3 mg/m ³ (Particulates (insoluble or poorly soluble)(NOS); USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Respirable fraction)
Not applicable		
Calcium Magnesium Hydroxide (39445-23-3)		
Not applicable		
Silicon Dioxide (14808-60-7)		
ACGIH	ACGIH TWA (mg/m ³)	0.025 mg/m ³ (Silica-Crystalline Quartz; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Respirable fraction)
OSHA	Remark (OSHA)	(3) See Table Z-3.

8.2. Exposure controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Hand protection	: protective gloves.
Eye protection	: Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH.
Respiratory protection	: Dust formation: dust mask.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: Yellowish-white crystals.
Colour	: Mixture contains one or more component(s) which have the following colour(s): Colourless to white White to grey Red-brown to black Pure substance: white Unpurified: coloured White
Odour	: odourless
Odour threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Vapour pressure	: No data available
Relative density	: No data available
Relative vapour density at 20 °C	: No data available
Solubility	: Water: Solubility in water of component(s) of the mixture : • Silicon Dioxide: insoluble • Aluminum Oxide (Non-Fibrous): < 0.01 g/100ml • Iron Oxide: < 0.1 g/100ml • Titanium Dioxide: 0.15 g/100ml • Portland cement: < 0.150 g/100ml
Log Pow	: No data available
Auto-ignition temperature	: No data available

UC-TG SILICA BLEND

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	: Not classified
Skin corrosion/irritation	: Causes skin irritation. Not classified.
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: May cause cancer (Inhalation).

UC-TG SILICA BLEND	
IARC group	1 - Carcinogenic to humans
National Toxicology Program (NTP) Status	2 - Known Human Carcinogens

Silicon Dioxide (14808-60-7)	
IARC group	1 - Carcinogenic to humans

Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified

Specific target organ toxicity (repeated exposure)	: Not classified
--	------------------

Aspiration hazard	: Not classified
Symptoms/injuries after skin contact	: Causes skin irritation.
Symptoms/injuries after eye contact	: May cause slight irritation.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: No environmental hazard.
-------------------	----------------------------

Portland cement (65997-15-1)	
LC50 fish 1	> 1000 mg/l (LC50; 96 h)

UC-TG SILICA BLEND

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.2. Persistence and degradability

UC-TG SILICA BLEND	
Persistence and degradability	Not established.
Portland cement (65997-15-1)	
Persistence and degradability	Biodegradability: not applicable. No (test) data on mobility of the substance available.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
calcium silicate clays (92704-41-1)	
Persistence and degradability	Biodegradability in soil: no data available.
Silicon Dioxide (14808-60-7)	
Persistence and degradability	Biodegradability: not applicable.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable

12.3. Bioaccumulative potential

UC-TG SILICA BLEND	
Bioaccumulative potential	Not established.
Portland cement (65997-15-1)	
Bioaccumulative potential	Bioaccumulation: not applicable.
calcium silicate clays (92704-41-1)	
Bioaccumulative potential	No bioaccumulation data available.

12.4. Mobility in soil

UC-TG SILICA BLEND	
Ecology - soil	No Data Available.

12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Contain and dispose of waste according to local regulations.
Waste disposal recommendations : Recycle/reuse.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT
Not regulated for transport

TDG

No additional information available

Transport by sea

No additional information available

Air transport

Proper Shipping Name (IATA) : Not Regulated

UC-TG SILICA BLEND

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 15: Regulatory information

15.1. US Federal regulations

UC-TG SILICA BLEND

Listed on the United States TSCA (Toxic Substances Control Act) inventory

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

Silicon Dioxide (14808-60-7)

Listed on IARC (International Agency for Research on Cancer)

15.3. US State regulations

UC-TG SILICA BLEND

U.S. - California - Proposition 65 - Carcinogens List	Yes
---	-----

U.S. - California - Proposition 65 - Developmental Toxicity	No
---	----

U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
---	----

U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No
---	----

Portland cement (65997-15-1)

U.S. - New Jersey - Right to Know Hazardous Substance List

Silicon Dioxide (14808-60-7)

U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

Other information : Disclaimer: This SDS to the best of our knowledge conforms to the requirements of OSHA 20 CFR 1910.1200 and summarizes the health and safety hazard information and general guidance on how to safely handle the material at the date of issue. Each user must review the SDS in the context of how the product will be handled and used in the workplace.


Full text of H-statements:

H315	Causes skin irritation
H350	May cause cancer

NFPA health hazard : 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.

NFPA fire hazard : 0 - Materials that will not burn.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



UC-TG SILICA BLEND

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

HMIS III Rating

Health	: 1 Slight Hazard - Irritation or minor reversible injury possible
Flammability	: 0 Minimal Hazard - Materials that will not burn
Physical	: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product