

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
 Product name : VE-SR-CLEAR  
 Product code : VE-SR-CLEAR  
 Other means of identification : VE-SR-CLEAR/50, VE-SR-CLEAR/5SF

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Protective Industrial Polymers  
 7875 Bliss Parkway  
 North Ridgeville, Ohio 44039 - USA-Ohio  
 T 440-327-0015  
[www.protectpoly.com](http://www.protectpoly.com)

#### 1.4. Emergency telephone number

Emergency number : Chemtrec: 800-427-9300 (Outside USA) 703-527-3887

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Flammable liquids H226  
 Category 3  
 Acute toxicity (oral) H302  
 Category 4  
 Skin corrosion/irritation H315  
 Category 2  
 Serious eye damage/eye irritation H319  
 Category 2A  
 Carcinogenicity H351  
 Category 2  
 Specific target organ toxicity (single exposure) Category 3 H335

Full text of H statements : see section 16

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Warning

Contains :

cobalt(II) ethylhexanoate; Styrene; Methacrylic Acid

Hazard statements (GHS-US) :

H226 - Flammable liquid and vapor  
 H302 - Harmful if swallowed  
 H315 - Causes skin irritation  
 H319 - Causes serious eye irritation  
 H335 - May cause respiratory irritation  
 H351 - Suspected of causing cancer

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use  
 P202 - Do not handle until all safety precautions have been read and understood  
 P210 - Keep away from sparks. - No smoking  
 P233 - Keep container tightly closed  
 P240 - Ground/bond container and receiving equipment  
 P241 - Use explosion-proof electrical equipment

# VE-SR-CLEAR

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P242 - Use only non-sparking tools  
P243 - Take precautionary measures against static discharge  
P261 - Avoid breathing vapors  
P264 - Wash hands, forearms and face thoroughly after handling  
P270 - Do not eat, drink or smoke when using this product  
P271 - Use only outdoors or in a well-ventilated area  
P280 - Wear protective clothing  
P301+P312 - If swallowed: Call a POISON CENTER if you feel unwell  
P302+P352 - If on skin: Wash with plenty of soap  
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P308+P313 - If exposed or concerned: Get medical advice/attention  
P312 - Call a doctor if you feel unwell  
P321 - Specific treatment (see on this label)  
P330 - Rinse mouth  
P332+P313 - If skin irritation occurs: Get medical advice/attention  
P337+P313 - If eye irritation persists: Get medical advice/attention  
P362+P364 - Take off contaminated clothing and wash it before reuse  
P370+P378 - In case of fire: Use to extinguish  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed  
P403+P235 - Store in a well-ventilated place. Keep cool  
P405 - Store locked up  
P501 - Dispose of contents/container to in accordance with local regulations

### 2.3. Other hazards

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/Information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product identifier	%	GHS-US classification
Styrene	(CAS No) 100-42-5	25 - 40	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335 Asp. Tox. 1, H304
Methacrylic Acid	(CAS No) 79-41-4	0 - 5	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311
cobalt(II) ethylhexanoate	(CAS No) 136-52-7	0 - 0.1	Carc. 2, H351

Full text of H-phrases: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor/physician if you feel unwell.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor/physician if you feel unwell.

First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Rinse mouth. Call a poison center/doctor/physician if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : May cause respiratory irritation.

Symptoms/injuries after skin contact : Irritation.

Symptoms/injuries after eye contact : Eye irritation.

# VE-SR-CLEAR

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapor.

Reactivity : Highly flammable liquid and vapor.

### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing vapors. Avoid contact with skin and eyes.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Avoid breathing vapors. Avoid contact with skin and eyes.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### cobalt(II) ethylhexanoate (136-52-7)

Not applicable

#### Styrene (100-42-5)

ACGIH	ACGIH TWA (ppm)	20 ppm (Styrene, monomer; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
ACGIH	ACGIH STEL (ppm)	40 ppm (Styrene, monomer; USA; Short time value; TLV - Adopted Value)
ACGIH	Remark (ACGIH)	CNS impair; URT irr; peripheral

# VE-SR-CLEAR

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Styrene (100-42-5)		
OSHA	Remark (OSHA)	(2) See Table Z-2.
Methacrylic Acid (79-41-4)		
ACGIH	ACGIH TWA (ppm)	20 ppm (Methacrylic acid; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
ACGIH	Remark (ACGIH)	Skin & eye irr

### 8.2. Exposure controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Hand protection	: Protective gloves.
Eye protection	: Safety glasses.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: In case of insufficient ventilation, wear suitable respiratory equipment.
Environmental exposure controls	: Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: clear
Odor	: styrene characteristic
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: ≈ 293 °F
Flash point	: ≈ 82 °F
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Solubility	: Water: Solubility in water of component(s) of the mixture : • N,N-dimethylaniline: 0.12 g/100ml (20 °C) • : 4.03 g/100ml (20 °C) • Stoddard solvent: insoluble • : 0.030 g/100ml • : 9.8 g/100ml (20 °C) • : 45 g/100ml • : >= 100 g/100ml (20 °C)
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Highly flammable liquid and vapor.

### 10.2. Chemical stability

Stable under normal conditions.

# VE-SR-CLEAR

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Oral: Harmful if swallowed.

<b>VE-SR-CLEAR</b>	
ATE US (oral)	1183.703 mg/kg body weight
<b>cobalt(II) ethylhexanoate (136-52-7)</b>	
LD50 oral rat	3129 mg/kg body weight (Rat; OECD 425: Acute Oral Toxicity: Up-and-Down Procedure; Experimental value)
LD50 dermal rat	> 2000 mg/kg body weight (Rat; Weight of evidence; OECD 402: Acute Dermal Toxicity)
ATE US (oral)	3129.000 mg/kg body weight
<b>Styrene (100-42-5)</b>	
LD50 oral rat	5000 mg/kg (Rat; Literature study; >6000 mg/kg bodyweight; Rat; Weight of evidence)
LD50 dermal rat	2820 mg/kg (Rat; Literature study; OECD 402: Acute Dermal Toxicity; >2000 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rabbit	5010 mg/kg (Rabbit; Literature study)
LC50 inhalation rat (mg/l)	12 mg/l/4h (Rat; Literature study)
LC50 inhalation rat (ppm)	2770 ppm/4h (Rat; Literature study)
ATE US (oral)	500.000 mg/kg body weight
ATE US (dermal)	2820.000 mg/kg body weight
ATE US (gases)	2770.000 ppmV/4h
ATE US (vapors)	12.000 mg/l/4h
ATE US (dust, mist)	12.000 mg/l/4h
<b>Methacrylic Acid (79-41-4)</b>	
LD50 oral rat	1060 mg/kg (Rat; Equivalent or similar to OECD 401; Experimental value; 1320 mg/kg bodyweight; Rat)
LD50 dermal rabbit	500 mg/kg body weight (Rabbit; Experimental value; Other; 500-1000 mg/kg bodyweight; Rabbit)
LC50 inhalation rat (mg/l)	7 mg/l/4h (Rat)
ATE US (oral)	1060.000 mg/kg body weight
ATE US (dermal)	500.000 mg/kg body weight
ATE US (vapors)	7.000 mg/l/4h
ATE US (dust, mist)	7.000 mg/l/4h

Skin corrosion/irritation : Causes skin irritation.  
Serious eye damage/irritation : Causes serious eye irritation.  
Respiratory or skin sensitization : Not classified  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Suspected of causing cancer.

<b>cobalt(II) ethylhexanoate (136-52-7)</b>	
IARC group	2B - Possibly carcinogenic to humans
<b>Styrene (100-42-5)</b>	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	3 - Reasonably anticipated to be Human Carcinogen

Reproductive toxicity : Not classified

# VE-SR-CLEAR

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Specific target organ toxicity (single exposure)	: May cause respiratory irritation.
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Symptoms/injuries after inhalation	: May cause respiratory irritation.
Symptoms/injuries after skin contact	: Irritation.
Symptoms/injuries after eye contact	: Eye irritation.

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

<b>cobalt(II) ethylhexanoate (136-52-7)</b>	
LC50 fish 1	46.51 mg/l (LOEC; ASTM; 96 h; Pimephales promelas; Flow-through system; Fresh water; Read-across)
EC50 Daphnia 1	0.212 mg/l (NOEC; ASTM; 48 h; Ceriodaphnia dubia; Static system; Salt water; Read-across)
LC50 fish 2	54.1 mg/l (LC50; ASTM; 96 h; Pimephales promelas; Flow-through system; Fresh water; Read-across)
EC50 Daphnia 2	0.605 mg/l (LC50; ASTM; 48 h; Ceriodaphnia dubia; Static system; Salt water; Read-across)
Threshold limit algae 1	144 µg/l (ErC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Pseudokirchneriella subcapitata; Static system; Fresh water; Read-across)
Threshold limit algae 2	32.2 µg/l (NOEC; OECD 201: Alga, Growth Inhibition Test; 72 h; Pseudokirchneriella subcapitata; Static system; Fresh water; Read-across)

<b>Methacrylic Acid (79-41-4)</b>	
LC50 fish 2	85 mg/l (LC50; EPA OTS 797.1400; 96 h; Salmo gairdneri; Flow-through system; Fresh water; Experimental value)
EC50 Daphnia 2	> 130 mg/l (EC50; EPA OTS 797.1300; 48 h; Daphnia magna; Flow-through system; Fresh water; Experimental value)
Threshold limit algae 1	45 mg/l (EC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Selenastrum capricornutum; Static system; Fresh water; Experimental value)

#### 12.2. Persistence and degradability

<b>cobalt(II) ethylhexanoate (136-52-7)</b>	
Persistence and degradability	Readily biodegradable in water. No (test)data on mobility of the substance available.

<b>Styrene (100-42-5)</b>	
Persistence and degradability	Readily biodegradable in water. Non degradable in the soil. Low potential for adsorption in soil. Photodegradation in the air.
Chemical oxygen demand (COD)	2.80 g O <sub>2</sub> /g substance
ThOD	3.07 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.42

<b>Methacrylic Acid (79-41-4)</b>	
Persistence and degradability	Readily biodegradable in water. Low potential for adsorption in soil. Photodegradation in the air.
Biochemical oxygen demand (BOD)	0.89 g O <sub>2</sub> /g substance
ThOD	1.67 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.5329 (Calculated value)

#### 12.3. Bioaccumulative potential

<b>VE-SR-CLEAR</b>	
Bioaccumulative potential	No test data available.

<b>cobalt(II) ethylhexanoate (136-52-7)</b>	
BCF fish 1	1.2 (BCF; 131 days; Seriola quinqueradiata; Static system; Salt water; Read-across)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

# VE-SR-CLEAR

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Styrene (100-42-5)</b>	
BCF fish 1	35.5 (BCF)
Log Pow	2.96 (Experimental value; OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method; 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

<b>Methacrylic Acid (79-41-4)</b>	
BCF other aquatic organisms 1	3 (BCF)
Log Pow	0.93 (Experimental value; 22 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

### 12.4. Mobility in soil

<b>cobalt(II) ethylhexanoate (136-52-7)</b>	
Surface tension	0.064 N/m (20 °C; 1 g/l)

<b>Styrene (100-42-5)</b>	
Surface tension	0.032 N/m (19 °C)
Log Koc	Koc,352; Estimated value; log Koc; 2.55; Estimated value

<b>Methacrylic Acid (79-41-4)</b>	
Surface tension	0.0659 N/m (20 °C; 1.01 g/l)

### 12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
Additional information : Flammable vapors may accumulate in the container.

## SECTION 14: Transport information

### Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1866 Resin solution (flammable), 3, III  
UN-No.(DOT) : UN1866  
Proper Shipping Name (DOT) : Resin solution  
flammable  
Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120  
Hazard labels (DOT) : 3 - Flammable liquid



Packing group (DOT) : III - Minor Danger  
DOT Packaging Non Bulk (49 CFR 173.xxx) : 173  
DOT Packaging Bulk (49 CFR 173.xxx) : 242

# VE-SR-CLEAR

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)	: B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672) T2 - 1.5 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 60 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 220 L
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel
Emergency Response Guide (ERG) Number	: 127
Other information	: No supplementary information available.

### TDG

No additional information available

### Transport by sea

No additional information available

### Air transport

No additional information available

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

#### VE-SR-CLEAR

Listed on the United States TSCA (Toxic Substances Control Act) inventory

SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard
-------------------------------------	---

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Styrene	CAS No 100-42-5	25 - 40%
---------	-----------------	----------

#### cobalt(II) ethylhexanoate (136-52-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### Styrene (100-42-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

CERCLA RQ	1000 lb
-----------	---------

#### Methacrylic Acid (79-41-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

### 15.2. International regulations

#### CANADA

#### VE-SR-CLEAR

WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	--

### EU-Regulations

No additional information available



# VE-SR-CLEAR

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### National regulations

#### Styrene (100-42-5)

Listed on IARC (International Agency for Research on Cancer)  
Listed as carcinogen on NTP (National Toxicology Program)

### 15.3. US State regulations

#### Styrene (100-42-5)

U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

#### Methacrylic Acid (79-41-4)

U.S. - New Jersey - Right to Know Hazardous Substance List

## SECTION 16: Other information

### Other information

: Disclaimer: This SDS to the best of our knowledge conforms to the requirements of OSHA 20 CFR 1910.1200 and summarizes the health and safety hazard information and general guidance on how to safely handle the material at the date of issue. Each user must review the SDS in the context of how the product will be handled and used in the workplace.

### Full text of H-phrases:

H226	Flammable liquid and vapor
H227	Combustible liquid
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H311	Toxic in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H351	Suspected of causing cancer

### NFPA health hazard


: 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

### NFPA fire hazard

: 3 - Liquids and solids that can be ignited under almost all ambient conditions.

### NFPA reactivity

: 2 - Normally unstable and readily undergo violent decomposition but do not detonate. Also: may react violently with water or may form potentially explosive mixtures with water.



### HMIS III Rating

#### Health

: 2 Moderate Hazard - Temporary or minor injury may occur

#### Flammability

: 3 Serious Hazard - Materials capable of ignition under almost all normal temperature conditions. Includes flammable liquids with flash points below 73 F and boiling points above 100 F, as well as liquids with flash points between 73 F and 100 F. (Classes IB & IC)

#### Physical

: 2 Moderate Hazard - Materials that are unstable and may undergo violent chemical changes at normal temperature and pressure with low risk for explosion. Materials may react violently with water or form peroxides upon exposure to air.

### SDS US (GHS HazCom 2012)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*