

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
 Product name : EPOXIDE RESIN 0075 BASE (7035)  
 Product code : EPOXIDE RESIN 0075 BASE  
 Other means of identification : COLOR: RAL 7035

#### 1.2. Recommended use and restrictions on use

No additional information available

#### 1.3. Supplier

Protective Industrial Polymers  
 7875 Bliss Parkway  
 North Ridgeville, Ohio 44039 - USA-Ohio  
 T 440-327-0015  
[www.protectpoly.com](http://www.protectpoly.com)

#### 1.4. Emergency telephone number

Emergency number : Chemtrec: 800-427-9300 (Outside USA) 703-527-3887

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Acute toxicity (oral) Category 4	H302	Harmful if swallowed
Skin corrosion/irritation Category 1A	H314	Causes severe skin burns and eye damage
Serious eye damage/eye irritation Category 2	H319	Causes serious eye irritation
Skin sensitization Category 1	H317	May cause an allergic skin reaction
Carcinogenicity Category 2	H351	Suspected of causing cancer
Hazardous to the aquatic environment - Acute Hazard Category 2	H401	Toxic to aquatic life
Hazardous to the aquatic environment - Chronic Hazard Category 2	H411	Toxic to aquatic life with long lasting effects

Full text of H statements : see section 16

#### 2.2. GHS Label elements, including precautionary statements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H302 - Harmful if swallowed  
 H314 - Causes severe skin burns and eye damage  
 H317 - May cause an allergic skin reaction  
 H319 - Causes serious eye irritation  
 H351 - Suspected of causing cancer  
 H401 - Toxic to aquatic life  
 H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use  
 P202 - Do not handle until all safety precautions have been read and understood  
 P260 - Do not breathe dust  
 P261 - Avoid breathing vapors  
 P264 - Wash hands, forearms and face thoroughly after handling  
 P270 - Do not eat, drink or smoke when using this product

# EPOXIDE RESIN 0075 BASE (7035)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P272 - Contaminated work clothing must not be allowed out of the workplace  
P273 - Avoid release to the environment  
P280 - Wear protective clothing  
P301+P312 - If swallowed: Call a doctor if symptoms persist. if you feel unwell  
P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting  
P302+P352 - If on skin: Wash with plenty of soap  
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P308+P313 - If exposed or concerned: Get medical advice/attention  
P310 - Immediately call a doctor if symptoms persist.  
P321 - Specific treatment (see a doctor if symptoms do not go away. on this label)  
P330 - Rinse mouth  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention  
P337+P313 - If eye irritation persists: Get medical advice/attention  
P363 - Wash contaminated clothing before reuse  
P391 - Collect spillage  
P405 - Store locked up  
P501 - Dispose of contents/container to in accordance with local regulations

### 2.3. Other hazards which do not result in classification

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Oxirane, 2,2'-(1-methylethylidene)bis(4,1[4-phenyleneoxymethylene])bis-, homopolymer	(CAS No) 25085-99-8	50 - 60	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1B, H317
Phenol,4-nonyl-,branched	(CAS No) 84852-15-3	25 - 30	Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Alkyl (C12-C14) Glycidyl Ether	(CAS No) 68609-97-2	< 5	Skin Irrit. 2, H315 Skin Sens. 1, H317
Titanium Dioxide	(CAS No) 13463-67-7	0 - 5	Carc. 2, H351
Carbon black	(CAS No) 1333-86-4	0.08 - 1	Carc. 2, H351
Solvent naphtha (petroleum), light aromatic	(CAS No) 64742-95-6	0.069 - 0.1	Flam. Liq. 2, H225 Resp. Sens. 1B, H334
Distillates (petroleum), hydrotreated middle	(CAS No) 64742-46-7	0.1104 - 0.1	Asp. Tox. 1, H304
1-methoxy-2-propyl acetate	(CAS No) 108-65-6	0.0115 - 0.01	Flam. Liq. 3, H226
Octamethylcyclotetrasiloxane	(CAS No) 556-67-2	0.000046 - 0.01	Flam. Liq. 3, H226

Full text of hazard classes and H-statements : see section 16

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures general : Call a poison center/doctor/physician if you feel unwell.  
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.  
First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.  
First-aid measures after eye contact : Rinse eyes with water as a precaution.  
First-aid measures after ingestion : Rinse mouth. Call a poison center/doctor/physician if you feel unwell.

### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/injuries after skin contact : Irritation. May cause an allergic skin reaction.

### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

# EPOXIDE RESIN 0075 BASE (7035)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

#### 5.2. Specific hazards arising from the chemical

Reactivity : The product is non-reactive under normal conditions of use, storage and transport.

#### 5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing vapors.

##### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Take up liquid spill into absorbent material.

Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid breathing vapors.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### Oxirane, 2,2'-(1-methylethylidene)bis(4,1[4-phenyleneoxymethylene])bis-,homopolymer (25085-99-8)

Not applicable

##### Alkyl (C12-C14) Glycidyl Ether (68609-97-2)

Not applicable

##### Phenol,4-nonyl-,branched (84852-15-3)

Not applicable

##### 1-methoxy-2-propyl acetate (108-65-6)

Not applicable

##### Solvent naphtha (petroleum), light aromatic (64742-95-6)

Not applicable

##### Distillates (petroleum), hydrotreated middle (64742-46-7)

Not applicable

##### Octamethylcyclotetrasiloxane (556-67-2)

Not applicable

# EPOXIDE RESIN 0075 BASE (7035)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Carbon black (1333-86-4)		
ACGIH	Local name	Carbon black
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	3 mg/m <sup>3</sup> (Inhalable fraction)
ACGIH	Remark (ACGIH)	Bronchitis
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	3.5 mg/m <sup>3</sup>
Titanium Dioxide (13463-67-7)		
ACGIH	Local name	Titanium dioxide
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
ACGIH	Remark (ACGIH)	LRT irr; A3
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup>

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.  
Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

#### Hand protection:

Protective gloves

#### Eye protection:

Safety glasses

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid  
Color : Mixture contains one or more component(s) which have the following colour(s):  
Light yellow Colourless Dark grey to black White Pure substance: white Unpurified: coloured  
Odor : There may be no odour warning properties, odour is subjective and inadequate to warn of overexposure.  
Mixture contains one or more component(s) which have the following odour:  
Mild odour Phenol odour Fruity odour Ether-like odour Petroleum-like odour Sweet odour Aromatic odour Odourless  
Odor threshold : No data available  
pH : No data available  
Melting point : Not applicable  
Freezing point : No data available  
Boiling point : 608 °F  
Flash point : 514 °F  
Relative evaporation rate (butyl acetate=1) : No data available  
Flammability (solid, gas) : Not applicable.  
Vapor pressure : No data available  
Relative vapor density at 20 °C : No data available  
Relative density : No data available  
Solubility : No data available  
Log Pow : No data available  
Auto-ignition temperature : No data available

# EPOXIDE RESIN 0075 BASE (7035)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Oral: Harmful if swallowed.

EPOXIDE RESIN 0075 BASE (7035)	
ATE US (oral)	500 mg/kg body weight
Oxirane, 2,2'-(1-methylethylidene)bis(4,1[4-phenyleneoxymethylene])bis-, homopolymer (25085-99-8)	
LD50 oral rat	> 2000 mg/kg (Rat, Literature study)
LD50 dermal rabbit	> 5000 mg/kg (Rabbit, Literature study)
Phenol,4-nonyl-,branched (84852-15-3)	
LD50 oral rat	1412 mg/kg body weight (Other, Rat, Male/female, Experimental value)
ATE US (oral)	1412 mg/kg body weight
1-methoxy-2-propyl acetate (108-65-6)	
LD50 oral rat	6190 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male/female, Experimental value)
LD50 dermal rabbit	> 5000 mg/kg body weight (Equivalent or similar to OECD 402, Rabbit, Male/female, Experimental value)
ATE US (oral)	6190 mg/kg body weight
Octamethylcyclotetrasiloxane (556-67-2)	
LD50 oral rat	> 4800 mg/kg (Equivalent or similar to OECD 401, Rat, Male, Experimental value)
LD50 dermal rat	> 2400 mg/kg body weight (Equivalent or similar to OECD 402, Rat, Male/female, Experimental value)
LC50 inhalation rat (mg/l)	36 mg/l (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male/female, Experimental value)
ATE US (vapors)	36 mg/l/4h
ATE US (dust, mist)	36 mg/l/4h
Carbon black (1333-86-4)	
LD50 oral rat	> 8000 mg/kg (Equivalent or similar to OECD 401, Rat, Male/female, Experimental value)
LD50 dermal rabbit	> 3000 mg/kg (Rabbit, Literature study)
LC50 inhalation rat (mg/l)	> 4.6 mg/l air (4 h, Rat, Experimental value)

# EPOXIDE RESIN 0075 BASE (7035)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Titanium Dioxide (13463-67-7)</b>	
LD50 oral rat	> 5000 mg/kg body weight (OECD 425: Acute Oral Toxicity: Up-and-Down Procedure, Rat, Female, Experimental value)
LC50 inhalation rat (mg/l)	> 6.82 mg/l (Other, 4 h, Rat, Male, Experimental value)
Skin corrosion/irritation	: Causes severe skin burns and eye damage.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer.

<b>Carbon black (1333-86-4)</b>	
IARC group	2B - Possibly carcinogenic to humans

<b>Titanium Dioxide (13463-67-7)</b>	
IARC group	2B - Possibly carcinogenic to humans

Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: Not classified

Specific target organ toxicity – repeated exposure	: Not classified
--	------------------

Aspiration hazard	: Not classified
-------------------	------------------

Symptoms/injuries after skin contact	: Irritation. May cause an allergic skin reaction.
--------------------------------------	--

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: Toxic to aquatic life with long lasting effects. Toxic to aquatic life.
-------------------	---

<b>Phenol,4-nonyl-,branched (84852-15-3)</b>	
LC50 fish 1	0.08 mg/l (ASTM E729-96, 96 h, Hybopsis monacha, Static system, Fresh water, Experimental value)
EC50 Daphnia 1	0.084 mg/l (ASTM E729-88, 48 h, Daphnia magna, Semi-static system, Fresh water, Experimental value)

<b>1-methoxy-2-propyl acetate (108-65-6)</b>	
LC50 fish 1	100 - 180 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value)
EC50 Daphnia 1	373 mg/l (Equivalent or similar to OECD 202, 48 h, Daphnia magna, Static system, Fresh water, Experimental value)

<b>Octamethylcyclotetrasiloxane (556-67-2)</b>	
LC50 fish 1	> 0.022 mg/l (EPA OTS 797.1400, 96 h, Oncorhynchus mykiss, Flow-through system, Fresh water, Experimental value)
EC50 Daphnia 1	> 0.015 mg/l (EPA OTS 797.1300, 48 h, Daphnia magna, Flow-through system, Fresh water, Experimental value)

<b>Carbon black (1333-86-4)</b>	
LC50 fish 1	> 1000 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Brachydanio rerio, Literature study)
EC50 Daphnia 1	> 5600 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 24 h, Daphnia magna, Static system, Fresh water, Experimental value)

<b>Titanium Dioxide (13463-67-7)</b>	
LC50 fish 1	> 100 mg/l (Equivalent or similar to OECD 203, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value)
ErC50 (algae)	61 mg/l (EPA 600/9-78-018, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value)

### 12.2. Persistence and degradability

# EPOXIDE RESIN 0075 BASE (7035)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Oxirane, 2,2'-(1-methylethylidene)bis(4,1[4-phenyleneoxymethylene]]bis-,homopolymer (25085-99-8)</b>	
Persistence and degradability	Not readily biodegradable in water.
<b>Phenol,4-nonyl-,branched (84852-15-3)</b>	
Persistence and degradability	Biodegradability in soil: no data available. Readily biodegradable in water.
<b>1-methoxy-2-propyl acetate (108-65-6)</b>	
Persistence and degradability	Readily biodegradable in the soil. Readily biodegradable in water.
<b>Octamethylcyclotetrasiloxane (556-67-2)</b>	
Persistence and degradability	Not readily biodegradable in water.
<b>Carbon black (1333-86-4)</b>	
Persistence and degradability	Biodegradability in soil: not applicable. Biodegradability: not applicable.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable
<b>Titanium Dioxide (13463-67-7)</b>	
Persistence and degradability	Biodegradability: not applicable.
Biochemical oxygen demand (BOD)	Not applicable (inorganic)
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)

### 12.3. Bioaccumulative potential

<b>Oxirane, 2,2'-(1-methylethylidene)bis(4,1[4-phenyleneoxymethylene]]bis-,homopolymer (25085-99-8)</b>	
Bioaccumulative potential	Not bioaccumulative.
<b>Phenol,4-nonyl-,branched (84852-15-3)</b>	
BCF fish 1	1200 - 1300 (OECD 305: Bioconcentration: Flow-Through Fish Test, 16 day(s), Gasterosteus aculeatus, Flow-through system, Salt water, Experimental value, Fresh weight)
Log Pow	5.4 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 23 °C)
Bioaccumulative potential	Potential for bioaccumulation (500 ≤ BCF ≤ 5000).
<b>1-methoxy-2-propyl acetate (108-65-6)</b>	
Log Pow	1.2 (Experimental value, Equivalent or similar to OECD 117, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
<b>Solvent naphtha (petroleum), light aromatic (64742-95-6)</b>	
Log Pow	2.1 - 6
<b>Octamethylcyclotetrasiloxane (556-67-2)</b>	
BCF fish 1	12400 (Other, 672 h, Pimephales promelas, Flow-through system, Experimental value, GLP)
Log Pow	4.45 - 5.1 (Literature)
Bioaccumulative potential	High potential for bioaccumulation (BCF > 5000).
<b>Carbon black (1333-86-4)</b>	
Bioaccumulative potential	Not bioaccumulative.
<b>Titanium Dioxide (13463-67-7)</b>	
Bioaccumulative potential	Not bioaccumulative.

### 12.4. Mobility in soil

<b>Oxirane, 2,2'-(1-methylethylidene)bis(4,1[4-phenyleneoxymethylene]]bis-,homopolymer (25085-99-8)</b>	
Ecology - soil	Low potential for mobility in soil.
<b>Phenol,4-nonyl-,branched (84852-15-3)</b>	
Log Koc	4.35 - 5.69 (log Koc, Other, Experimental value, GLP)
Ecology - soil	Adsorbs into the soil.

# EPOXIDE RESIN 0075 BASE (7035)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>1-methoxy-2-propyl acetate (108-65-6)</b>	
Surface tension	29.4 mN/m (20 °C, 100 vol %)
Log Koc	0.264 (log Koc, QSAR)
Ecology - soil	Highly mobile in soil.

<b>Octamethylcyclotetrasiloxane (556-67-2)</b>	
Log Koc	4.22 (log Koc, OECD 106: Adsorption/Desorption Using a Batch Equilibrium Method, Experimental value, GLP)
Ecology - soil	Low potential for mobility in soil.

<b>Carbon black (1333-86-4)</b>	
Ecology - soil	Adsorbs into the soil. Not toxic to plants. Not toxic to animals.

<b>Titanium Dioxide (13463-67-7)</b>	
Ecology - soil	Low potential for mobility in soil.

### 12.5. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

## SECTION 14: Transport information

### Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1760 Corrosive liquids, n.o.s. (Phenol,4-nonyl-,branched,Oxirane, 2,2'-(1-methylethylidene)bis(4,1[4-phenyleneoxymethylene])bis-,homopolymer), 8, III

UN-No.(DOT) : UN1760

Proper Shipping Name (DOT) : Corrosive liquids, n.o.s.  
Phenol,4-nonyl-,branched,Oxirane, 2,2'-(1-methylethylidene)bis(4,1[4-phenyleneoxymethylene])bis-,homopolymer

Class (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136

Packing group (DOT) : III - Minor Danger

Hazard labels (DOT) : 8 - Corrosive



Dangerous for the environment : Yes

Marine pollutant : Yes



DOT Packaging Non Bulk (49 CFR 173.xxx) : 203

DOT Packaging Bulk (49 CFR 173.xxx) : 241

DOT Symbols : G - Identifies PSN requiring a technical name



# EPOXIDE RESIN 0075 BASE (7035)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)	: IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31H21 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 154
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 60 L
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other	: 40 - Stow "clear of living quarters"
Emergency Response Guide (ERG) Number	: 154
Other information	: No supplementary information available.

### TDG

Not applicable

### Transport by sea

Transport document description (IMDG)	: UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., 9, III
UN-No. (IMDG)	: 3082
Proper Shipping Name (IMDG)	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
Class (IMDG)	: 9 - Miscellaneous dangerous compounds
Packing group (IMDG)	: III - substances presenting low danger
Limited quantities (IMDG)	: 5 L
Marine pollutant	: Yes



### Air transport

Transport document description (IATA)	: UN 3082 Environmentally hazardous substance, liquid, n.o.s., 9, III
UN-No. (IATA)	: 3082
Proper Shipping Name (IATA)	: Environmentally hazardous substance, liquid, n.o.s.
Class (IATA)	: 9 - Miscellaneous Dangerous Goods
Packing group (IATA)	: III - Minor Danger

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

#### EPOXIDE RESIN 0075 BASE (7035)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

# EPOXIDE RESIN 0075 BASE (7035)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Oxirane, 2,2'-(1-methylethylidene)bis(4,1[4-phenyleneoxymethylene])bis-,homopolymer (25085-99-8)</b>	
EPA TSCA Regulatory Flag	XU - XU - indicates a substance exempt from reporting under the Inventory Update Reporting Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(C)).

<b>Phenol,4-nonyl-,branched (84852-15-3)</b>
Subject to reporting requirements of United States SARA Section 313

<b>1-methoxy-2-propyl acetate (108-65-6)</b>	
EPA TSCA Regulatory Flag	P - P - indicates a commenced PMN substance.

### 15.2. International regulations

#### CANADA

<b>Oxirane, 2,2'-(1-methylethylidene)bis(4,1[4-phenyleneoxymethylene])bis-,homopolymer (25085-99-8)</b>
Listed on the Canadian DSL (Domestic Substances List)

<b>Alkyl (C12-C14) Glycidyl Ether (68609-97-2)</b>
Listed on the Canadian DSL (Domestic Substances List)

<b>Phenol,4-nonyl-,branched (84852-15-3)</b>
Listed on the Canadian DSL (Domestic Substances List)

<b>1-methoxy-2-propyl acetate (108-65-6)</b>
Listed on the Canadian DSL (Domestic Substances List)

<b>Solvent naphtha (petroleum), light aromatic (64742-95-6)</b>
Listed on the Canadian DSL (Domestic Substances List)

<b>Distillates (petroleum), hydrotreated middle (64742-46-7)</b>
Listed on the Canadian DSL (Domestic Substances List)

<b>Octamethylcyclotetrasiloxane (556-67-2)</b>
Listed on the Canadian DSL (Domestic Substances List)

<b>Carbon black (1333-86-4)</b>
Listed on the Canadian DSL (Domestic Substances List)

<b>Titanium Dioxide (13463-67-7)</b>
Listed on the Canadian DSL (Domestic Substances List)

#### EU-Regulations

No additional information available

#### National regulations

<b>Carbon black (1333-86-4)</b>
Listed on IARC (International Agency for Research on Cancer)

<b>Titanium Dioxide (13463-67-7)</b>
Listed on IARC (International Agency for Research on Cancer)

### 15.3. US State regulations

<b>Carbon black (1333-86-4)</b>					
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)	Maximum Allowable Dose Limit (MADL)
Yes	No	No	No		

# EPOXIDE RESIN 0075 BASE (7035)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Titanium Dioxide (13463-67-7)					
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)	Maximum Allowable Dose Limit (MADL)
Yes	No	No	No		

### Carbon black (1333-86-4)

U.S. - New Jersey - Right to Know Hazardous Substance List

### Titanium Dioxide (13463-67-7)

U.S. - New Jersey - Right to Know Hazardous Substance List

## SECTION 16: Other information

Other information

: Disclaimer: This SDS to the best of our knowledge conforms to the requirements of OSHA 20 CFR 1910.1200 and summarizes the health and safety hazard information and general guidance on how to safely handle the material at the date of issue. Each user must review the SDS in the context of how the product will be handled and used in the workplace.

Full text of H-phrases:

H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H351	Suspected of causing cancer
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects

NFPA health hazard


: 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.

NFPA fire hazard

: 1 - Must be preheated before ignition can occur.

NFPA reactivity

: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given

Flammability : 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)

Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

SDS US (GHS HazCom 2012)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*